Industrial / Power / Data / Security / Fibre

Part No: MC147S-W

Description	Stranded 21AWG PACW, 7Cores, PVC Insulation, Aluminium Polyester
	Tape Overall Screen, Stranded 24AWG TACW Drain Wire, PVC Sheath,

AS/ACIF S008, BS4737-3.30 Applicable Standards

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as

Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

garland MC147S



Cable Construction Relative Parts



Conductor Insulation Polyester Tape Drain Wire Al. Foil Sheath





	A1A/C	Chronding	A === (== == 2)	Diamotor(mana)	Matarial
Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	21	14/0.2	0.44	0.87	PACW
Insulation	Cores: 7 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green, Brown Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5				
Screen	Material : Al. Polyester Tape		Coverage: 100%		
Drain Wire	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
Diani wire	24	7/0.2	0.22	0.6	PACW

With Garland, you are always well connected.





Industrial / Power / Data / Security / Fibre

PVC Grey (mm) : 0.7 6.6	
----------------------------------	--

Mechanical Properties	
Operating Temperature Range	-15 to 70℃
Max. Recommended Pulling Tension	215N
Min. Bend Radius (install)	65.5mm
Approximate Mass	7.0kg/100m

SKU	Jacket Colour	Length (Metres)	Carton/Box Size (cm)	Reels/Carton	Boxes x Reels per Pallet
MC147S100W	Grey	100	46 x 24 x 17	2	40 x 2
MC147S250W	Grey	250	36 x 36 x 19	1	45 x 1 or 36 x 1
MC147S500W	Grey	500	39 x 39 x 29.5	1	12 x 1

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances