



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC7042FRSHFRD

2 cores x 1.0mm² stranded PACW, LSZH (X-HF-110) insulated, cabled, overall screened with an Aluminium laminate tape and 7/0.25mm tinned annealed copper draing wire, overall LSZH (X-HFS-110-TP) Description sheathed, WS51-W rated 2 hour fire resistant screened cable to AS 3013.

Applicable Standards AS 1670, AS/NZS 3013, AS/NZS 3808, AS/CA S-008, AS 1049

Used for fire alarm systems where prolonged exposure to fire and Suitable Applications sprinklers is required.

Cable Construction Drawing







Cable Description				
Conductor	Nominal Conductor Area (mm²)	# of Strands	Material	Conductor Class
	1.0	7	PACW	2
Insulation	# Cores : Material : Colour : Nominal OD (mm) :	2 LSZH X-HF-1 Wire 1: Rec Wire 2: Wh 3.7		r
Screen	Material: Alum Coverage: 100%	inium Polyester I 6	_aminate	

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the

experts' choice for high quality cables.

Drain Wire	AWG Sta		iding	Material	
	22	7/0.25		TACW	
Sheath	Material:		HFS-110-TP (LSZH) UV stabilized		
	Colour:		Red (RAL 3000)		
	Diameter:		10.3 mm		

Electrical Properties	
Max. Conductor DC Resistance @ 20°C	18.1 Ω/km
Voltage Rating	450/750V
Mechanical Properties	
Operating Temperature Range	-15 to 110℃
AS 3013 rating	WS51-W
Max. Recommended Pulling Tension	240N
Min. Bend Radius (install)	140mm
Approximate Mass	14.6kg/100m
Supply Information	

Dimensions

F55 x 32 cm

Madison reserves th	e right to make	changes to the	products described	d in this specification	without
prior notice					

Pack Type

Wooden Drum

All values subject to factory tolerances

Pack Size

500m



Packs Per Pallet

8 or 12