



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

## Part No: MC74BN

Description Stranded 24AWG (7/0.2mm) PACW, 4 Cores, PVC Insulation, PVC Sheath.


Applicable Standards AS/CA S008, BS4737-3.30, AS 1049

Suitable Applications For telecommunications system

#### **Cable Construction Drawing**

#### **Cable Construction Relative Parts**











Cable D	escription
---------	------------

Conductor	AWG	Standing	Area(mm <sup>2</sup> )	Diameter(mm) Mate	
	24	7/0.2mm	0.22	0.6	PACW
Insulation	Cores: 4 Material: PVC Colour: White, Blue, Red, Black Nominal Thickness (mm): 0.28 Nominal OD (mm): 1.2				
Sheath	Material: PVC Colour: Terra Brown (RAL 8028) Nominal Thickness (mm): 0.36 Nominal OD (mm): 3.6				

With Garland, you are always well connected.







### Industrial / Power / Data / Security / Fibre

# **Garland's Pro Series** range is the experts' choice for high quality cables.

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	93.3Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.5 kV ac/1min
Voltage Test: Core to sheath	3.0 kV ac/1min

Mechanical Properties	
Operating Temperature Range	-15 to 70℃
Max. Recommended Pulling Tension	56N
Min. Bend Radius (install)	36mm
Approximate Mass	1.92kg/100m
Sheath Printing	GARLAND SECURITY CABLE MC74 - 4 X 7/0.2 24AWG - MM/YYYY - "Mmark"

Supply Information				
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Plastic Reel	10 x 4.5 x 2"	8R	
300m	Reel Box	13 x 13 x 7.5"	1Box	
500m	Wooden Reel	W42 x H21.8cm	1R	

Document Change Record	Issue	Date	Prepared by	Approved By
	01	28-11-2012		Pent
Change History	Issue	Change		

With Garland, you are always well connected.

