



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC76GY

Description Stranded 24AWG (7/0.2mm) PACW, 6Cores, PVC Insulation, PVC Sheath.

Applicable Standards AS/CA S-008, BS4737-3.30, AS 1049

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description

Conductor	AWG	Standing	Area(mm ²)	Diameter(mm)	Material
	24	7/0.2mm	0.22	0.6	PACW
Insulation	Cores: 6 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green Nominal Thickness (mm): 0.28 Nominal OD (mm): 1.2			Green	
Sheath		: Thickness (mn OD (mm) :	PVC Grey(RAL 70 n): 0.5 4.9	46)	

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	93.3Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.5 kV ac/1min
Voltage Test: Core to sheath	3.0 kV ac/1min

Mechanical Properties	
Operating Temperature Range	-15 to 70°C
Max. Recommended Pulling Tension	92N
Min. Bend Radius (install)	49mm
Approximate Mass	3.2kg/100m
Sheath Printing	GARLAND SECURITY CABLE MC76 - 6 X 7/0.2 24AWG - MM/YYYY - "Mmark"

Supply Information					
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet	
100m	Plastic Reel	10 x 4.5 x 3"	6R	32	
300m	Reel Box	14.5 x 14.5 x 7.5"	1Box	45Box	
500m	Wooden Reel	W33 x 21.8cm	1R	36	

Document Change Record	Issue	Date	Prepared by	Approved By
	01	29-11-2012	YDM	Pent
Change History	Issue	Change		

With Garland, you are always well connected.

