Data Cable





Part No: MC76S-W

Description Stranded 24AWG TACW, 6 Cores, PVC Insulation, Aluminium Polyester Tape

Overall Screen, 24AWG TACW Drain Wire, PVC Sheathed RS-232 style data

cable.

Applicable Standards AS/ACIF S008, EIA-RS232

Suitable Applications Indoor data cable for use in connecting DTE such as computer

terminals, printers, modems, fax machines, keyboards and monitors. Designed for low bit rate data signals including serial


data bus systems such as EIARS232

Also used in security systems to connect sensors and keypads to

central monitors.

mages





Picture is for illustration only.

For actual jacket colours, please refer to Supply Information Table.





	Conductor	Material	TACW 7		
		No. of Strands			
		Strand Size	0.2 mm		
	Insulation	Cores	6		
u		Material	V-75 PVC		
sctic		Colour	White, Blue, Red, Black, Yellow, Green		
Construction		Average Thickness (mm)	0.3		
Con		Diameter (mm)	1.1		
	Wrapping Tape	Material	Polyester Tape		
		Application	Longitudinal or Helical		
		Minimum Overlap	20%		
	Drain Wire	Material	TACW		
		No. of Strands	7		
		Strand Size	0.2 mm		



Garland's Work Series range is the experts' choice for high quality cables.

Data Cable





	Screen	Material	Aluminium-Polyester Laminate Tape, Alumimium facing in	
Construction		Application	Longitudinal or Helical	
		Minimum Overlap	20%	
	Sheath	Material	4V-75 PVC	
		Colour	Refer to Supply Information Table	
		Diameter (mm)	5.4 mm	
		Nominal Thickness (mm)	0.7 mm	

Properties	Voltage Rating	ELV
	Operating Temperature Range	-15 to 75°C
	Max. Recommended Pulling Tension	92N
	Min. Bend Radius (install)	55 mm
	Approximate Mass	4.3kg/100 m

Supply Information	Part Number	Pack Size	Jacket Colour	Pack Type	Carton/Reels	Boxes x Reels Per Pallet
	MC76S100W	100m	Grey	Plastic Reel	4	28 x 4 or 24 x 4
	MC76S300BW	300m	Grey	Pull Box	-	36
	MC76S500W	500m	Grey	Plywood Reel	1	16 x 1

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

