



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC76WH

Stranded 24AWG (7/0.2mm) PACW, 6Cores, PVC Insulation, PVC Sheath. Description

Applicable Standards AS/CA S008, BS4737-3.30, AS 1049

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description							
Conductor	AWG	Standing	Area(mm ²)	Diameter(mm)	Material		
	24	7/0.2mm	0.22	0.6	PACW		
Insulation	l .	: Thickness (mm OD (mm) :	6 PVC White, Blue, Red, Black, Yellow, Green m): 0.28 1.2				
Sheath		: Thickness (mm OD (mm) :	PVC White n): 0.5 4.9				

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical Properties			
Voltage Rating	ELV		
Max. Conductor DC Resistance @ 20°C	93.3Ω/km		
Min. Insulation Resistance @ 20°C	50MΩ.km		
Voltage Test: Conductor to core	1.5 kV ac/1min		
Voltage Test: Core to sheath	3.0 kV ac/1min		
Mechanical Properties			
Operating Temperature Range	-15 to 70℃		
Max. Recommended Pulling Tension	92		
Min. Bend Radius (install)	49mm		
Approximate Mass	3.2kg/100m		
Sheath Printing	GARLAND SECURITY CABLE MC76 - 6 X 7/0.2 24AWG - MM/YYYY - "Mmark"		

Supply Information									
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet					
100m	Plastic Reel	10 x 4.5 x 3"	6R	32					
300m	Reel Box	14.5 x 14.5 x 7.5"	1Box	45Box					
500m	Wooden Reel	W33 x 21.8cm	1R	36					

Document Change Record	Issue	Date	Prepared by	Approved By
	01	29-11-2012	YDM	Pent
Changa History	Issue	Change		
Change History				

With Garland, you are always well connected.

