



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

## Part No: MC78GY

Description Stranded 24AWG (7/0.2mm) PACW, 8Cores, PVC Insulation, PVC Sheath.


AS/CA S-008, BS4737-3.30, AS 1049 Applicable Standards

Suitable Applications For the interconnection of control equipment and Instruments.

#### **Cable Construction Drawing**

#### **Cable Construction Relative Parts**











Cable Description					
Conductor	AWG	Standing	Area(mm <sup>2</sup> )	Diameter(mm)	Material
	24	7/0.2mm	0.22	0.6	PACW
Insulation	Cores: 8 Material: PVC Colour: White, Blue, Red, Black, Yellow, Brown, Green, Violet Nominal Thickness (mm): 0.28 Nominal OD (mm): 1.2			Brown,	
Sheath		: Thickness (mr OD (mm) :	PVC Grey(RAL 70 n): 0.6 5.4	146)	

With Garland, you are always well connected.







### Industrial / Power / Data / Security / Fibre

# **Garland's Pro Series** range is the experts' choice for high quality cables.

ELV
93.3Ω/km
50MΩ.km
1.5 kV ac/1min
3.0 kV ac/1min

Mechanical Properties			
Operating Temperature Range	-15 to 70°C		
Max. Recommended Pulling Tension	123N		
Min. Bend Radius (install)	54mm		
Approximate Mass	4.3kg/100m		
Sheath Printing	GARLAND SECURITY CABLE MC78 - 8 X 7/0.2 24AWG - MM/YYYY - "Mmark"		

Supply Information						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet		
100m	Plastic Reel	10 x 4.5 x 4"	4R			
500m	Wooden Reel	W36 x H21.8	1R			

Document Change Record	Issue	Date	Prepared by	Approved By
	01	29-11-2012	LLS	Pent
Change History	Issue	Change		
Change History				

With Garland, you are always well connected.

