



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: TSCW24

Description	Stranded 0.75mm ² PACW, 2 Core, V-75 PVC Insulation, 4V-75 PVC Sheath.
Applicable Standards	AS/ACIF S008, AS 1049
Suitable Applications	For the wiring of electronic and allied equipment, extension speakers, security systems, etc.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description						
Conductor	AWG	Area(mm ²)	Stranding	Diameter(mm)	Material	
	19	0.75	24/0.2	1.13	PACW	
Insulation	Cores:		2			
	Material	:	V-75 PVC	V-75 PVC		
	Colour:		Red, Wh	Red, White		
	Nominal	Thickness (mm)	: 0.5	0.5		
	Minimum Thickness (mm):): 0.4	0.4		
	Nominal	OD (mm):	2.2±0.1			

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Material: 4V-75 PVC

Colour: Red

Sheath Nominal Thickness (mm): 0.5

Minimum Thickness (mm): 0.4

Nominal OD (mm): $3.3 \times 5.4\pm0.2$

Electrical Properties			
Voltage Rating	ELV		
Max. Conductor DC Resistance @ 20°C	29.1Ω/km		
Min. Insulation Resistance @ 20°C	50MΩ.km		
Voltage Test: Conductor to core	1.5 kV ac/1min		
Voltage Test: Core to sheath	3.0 kV ac/1min		

Mechanical Properties	
Operating Temperature Range	-15 to 75℃
Max. Recommended Pulling Tension	105N
Min. Bend Radius (install)	33mm
Approximate Mass	3.4kg/100m
Sheath Printing	rcm GARLAND TWIN SHEATHED TSCW24 - 2 X 24/0.2mm - "Mmark" – "batch"

Sheath Colour	
TSCW24BL	Colour : Blue
TSCW24BN	Colour : Brown
TSCW24RD	Colour : Red
TSCW24RDBL	Colour : Red/Blue Stripe
TSCW24WH	Colour : White

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Supply Information				
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Wooden Reel	10 x 4.5 x 2.5"	4R	48R
500m	Wooden Reel	W30 x H21.8cm	1R	46R

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances