#### **Product data sheet**



## 1035W-N

#### Miniature self adhesive magnetic contact

#### **Self-Adhesive Contact**

The Sentrol 1035 series magnetic contacts saves installation time through the use of a specially formulated 3M adhesive tape. The tape, which establishes a permanent bond between the contact and the surface, can be repositioned during the first 5 minutes. A low profile and small footprint combine with reliable Sentrol technology to make the 1035 series the perfect magnetic contact for those situations where drilling holes is impractical.

#### **Durability and dependability**

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

#### High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



#### **Details**

- Quick tape mounting, no screws or glues needed
- Convenient surface mounting
- · Urethane/acrylic tape bonding improves with age
- Tamper loop provided (depending on type)

# 1035W-N

## Miniature self adhesive magnetic contact

## **Technical specifications**

Can distance (may)	
Gap distance (max	·
	25 mm
Connections	
	30 cm wire leads
Contact	
	NC
Supervised loop	
	No
Dimensions (L x W x H)	
	38 x 6 x 9 mm
Color	
	White



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.