#### **Product data sheet**



# 1125W-N

### "Stubby" press-fit recessed mount magnetic contact

#### Stubby "Press-Fit" contact

The Sentrol 1125 series "Stubby" Press-Fit magnetic contacts are a 9 mm switch designed specifically for applications where space is limited. The short length makes it ideal for thin-framed windows and doors where longer units cannot be used. Press fit ribs on the housing make for quick, easy installation.

#### Easy installation

Switch is hermetically sealed reed switch, which is potted using exclusive polyurethane potting compound into the switch housing. Switch and Alnico V magnet is drill-mounted in wood or aluminum with a suitable adhesive. The switch and magnet housing have three fins to press-fit against the mounting hole.

#### **Durability and dependability**

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

#### High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



#### **Details**

- · Quick and easy to install
- Unobtrusive and attractive design

# 1125W-N

## "Stubby" press-fit recessed mount magnetic contact

## **Technical specifications**

	19 mm	
Connections		
	30 cm wire leads	
Contact		
	NC	
Supervised lo	ор	
	No	
Dimensions (	Ø x L)	
Contact	Ø 9 x 19 mm	
Magnet	Ø 9 x 19 mm	
Color		



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.